



Day Tank

Standard Equipment

- Double wall tank.
- 150% rupture basin.
- 2 GPM pump, 1/3 HP, 120 VAC motor.
- Dip Tube Supply/Return Fitting Package.
- High/low pump and on/off float assembly.
- Mounted Series 400 Controller.
- Rochester fuel level gauge.
- Fuel in basin alarm.
- 2" NPT normal vent cap.
- 1" NPT overflow fitting.
- Emergency pressure relief cap.
- 2" NPT locking manual fill cap.
- 1/2" NPT basin drain.
- 1/2" Y-type fuel strainer.
- 1/2" Solenoid valve.
- 1/2" Check valve.
- Extra pipe connection.
- Forest green paint finish.

Optional Equipment

- Reverse pump system.
- Duplex pump system.
- Extended fill port.
- 2" NPT vent whistle.
- 2" NPT overflow prevention valve.
- 2" NPT skully connector.
- Multiple size dip tube packages.
- Immersion heater with thermostat.
- 5-gallon spill box (tank mount).
- 5-gallon spill box (remote mount).
- 200% rupture basin.
- 4 GPM pump, 1/3 HP, 120VAC motor.
- 7 GPM pump, 1/2 HP, 120VAC motor.
- 16 GPM pump, 1 HP, 120VAC motor.
- 23 GPM pump, 1 1/2 HP, 120VAC motor.
- Remote pump/motor mounting base.
- Aluminum cover for electronics.
- Optional colors are available.
- Contact Global Power Components for any options that are not listed. We will work with you, regardless of what you need, to meet the requirements that you desire.