



Generator Transport Trailer

Standard Equipment

- Trailers are designed to fit the specific generators being transported.
- Single Wall Fuel Cell.
- Maximum wet weight capacity 24,000 lbs.
- Single, double, or triple axle trailer available.
- Torflex Axel with radial tires.
- Electric Breaks.
- Electric Break Away Kit.
- One tongue jack and two rear leveling stabilizer jacks.
- Safety chains.
- Tongue mounted utility box.
- Safety chains.
- Supply and Return Dip Tube Package.
- Rochester fuel level gauge and low fuel level alarm with alarm set at 50% tank capacity.
- DOT light package.
- DOT fill cap.
- 2 5/16" adjustable/interchangeable coupler.
- 3" pintel eye coupler.
- 7-pin trailer plug.
- Equipped with tie down provisions for the appropriate weight.
- License plate lighting and bracket.
- Black paint finish.

Optional Equipment

- Double Wall fuel cell with leak detection sensor and Leak Alarm Panel with visual and audible alarms.
- "I" beam generator support.
- Hydraulic Surge Breaking System.
- Tongue mounted spare tire.
- Immersion heater with thermostat.
- Rear mounted cable box.
- Dolly wheel.
- Parking break.
- 6-pin Pollard connector.
- Colors available to match the generator.
- Contact Global Power Components for any options that are not listed. We will work with you, regardless of what you need, to meet the requirements that you desire.