



Sub-Base Day Tank

Standard Equipment

- Double wall.
- Dip Tube Supply/Return Fitting Package.
- Rochester fuel level gauge.
- Fuel in basin alarm.
- 2" NPT normal vent cap.
- Emergency pressure relief caps.
- 2" NPT locking manual fill cap.
- ½" NPT basin drain.
- Flush mount-lifting plate.
- 2" NPT Fitting Package for installation flexibility.
- 1" NPT overflow fitting.
- 2 GPM pump, 1/3 HP, 120 VAC motor.
- High/low pump and on/off float assembly.
- Mounted Series 400 Controller.
- ½" Y-type fuel strainer.
- ½" Solenoid valve.
- ½" Check valve.
- Extra pipe connection.

Optional Equipment

- Electrical stub up.
- Removable end plate.
- 2" NPT vent whistle.
- Inspection port.
- Multiple size dip tube package.
- Flanged channels for enclosure mounting.
- Top mount basin alarm.
- Immersion heater with thermostat.
- Extended fill port.
- 5-gallon spill box (tank mount).
- 5-gallon spill box (remote mount).
- Remote alarm fill station.
- Diamond plate top cover.
- Isopad support plate.
- Internal stiffener support channels.
- Pressure test basin.
- Reverse pump system.
- Duplex pump system.
- 150% and 200% rupture basin.
- 4 GPM pump, 1/3 HP, 120VAC motor.
- 7 GPM pump, 1/2 HP, 120VAC motor.
- 16 GPM pump, 1 HP, 120VAC motor.
- 23 GPM pump, 1 1/2 HP, 120VAC motor.
- Remote pump/motor mounting base.
- Aluminum cover for electronics.
- Optional colors are available.
- Contact Global Power Components for any options that are not listed. We will work with you, regardless of what you need, to meet the requirements that you desire.